

Model: S4-3HD



Features



- DVB-S/S2 Compliant (MPEG-2 / MPEG-4 / H.264)
- SCPC & MCPC receivable from KU and C band satellites
- DiSEqC 1.0 / 1.1 / 1.2 / 1.3 (USALS)
- 3D GPU Graphic Processor to support 3D user interfaces & games
- UniCable supported
- Support multi satellite search, network search, PID search, Manual search, multi-TP - & Blind search
- Variable aspect ratio (4:3 / 16:9) with PAN&SCAN vector or Letter Box option
- 16 bits color On Screen Display (OSD)
- 1 Favorite group and parental lock supported
- PAL / NTSC / SECAM
- True Full color (32bits) On Screen Display (OSD)
- Multi language MENU/OSD support (English, German, Turkish, Polish, Italian, Dutch etc....)
- Multi Language audio
- Multi Language DVB Subtitle output
- Timer function supported
- 7 days EPG
- Teletext through VBI & OSD
- USB for firmware upgrade (data, kernel, file system) through USB or Ethernet
- USB WIFI supported
- 1 * USB 2.0 interface
- TV APP (Video On Demand VOD, Audio streaming, Social Networking, Personal Interest, Local content partnership)

Specifications



Processor & Memory

- Flash: 8MB
- SDRAM: 128MB

Tuner & Channel

- Tuner: GSXA-30R

Audio

- Standard: ISO/IEC 13818-3
- Sampling Frequency: 32, 41.1, 48KHz
- Audio Output Impedance: Low
- Output Mode: Mono, Dual Channel, Stereo, Left and Right

Video

- Standard: ISO/IEC 13818-2
- MPEG-1, MPEG-2 MP@ML, H.264, VCI, DV, DivX and MPEG-4
- Video Full resolution
- HDMI output with upscale supporting up to 1080p 60Hz

A/V Output

- Video De-emphasis: CCIR TEC: 405-1, 625 lines
- Video Bandwidth: 5,5 MHz
- Video Output impedance: 75 Ohm'
- Video Output level: 1.0Vpp
- Audio Output frequency: 20Hz ~ 20KHz

Data In/Out

- Audio connectors: Audio L/R, SPDIF (Coaxial)
- Video connectors: CVBS, HDMI, TV Scart (CVBS+RGB)
- Other connectors: 1 * USB, Tuner In/Out

Power Supply

- Power type: SMPS
- Input Voltage: AC 100 ~ 240V, 50/60Hz
- Power Consumption: Max. 25W
- Power consumption standby: < 0,5W
- Output: European outlet