

Model: S4-17HD



Features

- DVB-S/S2 Compliant (MPEG-2 / MPEG-4 / H.264)
- SCPC & MCPC receivable from KU and C band satellites
- Universal, Single Ku & C Band Wideband LNB
- Sensitive tuner with loop through
- DiSEqC 1.0 / 1.1 / 1.2 / 1.3 (USALS)
- UniCable supported
- PAL / NTSC
- Blind Search supported
- Variable aspect ratio (4:3 / 16:9) with PANSCAN vector or Letter Box.
- Multi language MENU/OSD support (English, German, Turkish, Polish, Italian, Dutch etc....)
- Multi Language audio
- Multi Language Subtitle supported
- Multi Media supported
- Multi Picture supported
- 8 Favorite groups and parental lock supported
- Easy functions such as Group move and Recall History
- Timer function supported
- 7 days EPG
- Parental guide and rating control
- USB for firmware upgrade & PVR
- Teletext through VBI & OSD
- 3G/IPTV optional
- Conditional Access Interface (CA)
- USB WIFI supported

Specifications

Processor & Memory

- Flash: 8 MByte
- DDRII memory: 64M*1600MHz

Audio

- Standard: ISO/IEC 13818-3
- Sampling Frequency: 32, 41.1, 48KHz
- Audio Output Impedance: Low
- Output Mode: Mono, Dual Channel, Stereo, Left and Right

Video

- Standard: ISO/IEC 13818-2
- MPEG-1, MPEG-2 MP@ML, H.264, VCI, DV, DivX and MPEG-4
- Host Supplied Audio/Video : I & P frame support
- HDMI output with upscale supporting up to 480p & 380i, 576p & 576i, 720p & 1080i & 1080p 50Hz

A/V Output

- Video De-emphasis: CCIR TEC: 405-1, 825 lines
- Video Bandwidth: 5,5 MHz
- Video Output impedance: 75 Ohm'
- Video Output level: 1.0Vpp
- Audio Output frequency: 20Hz ~ 20KHz

Data In/Out

- Audio connectors: Audio L/R, SPDIF (Coaxial / Optical)
- Video connectors: CVBS, HDMI
- Other connectors: 1 * USB, Tuner In/Out, RS232, RJ45

Power Supply

- Power type: SMPS
- Input Voltage: AC 100 ~ 240V, 50/60Hz
- Power Consumption: Max. 20W
- Power consumption standby: < 0,5W
- Output: European outlet

Packaging information

- Receiver dimensions: 289 * 20 * 262mm
- Pcs per carton: 10
- Giftbox dimensions: 296 * 78 * 260mm