

Model: S11-3HD



Features



- DVB-S/S2 Compliant (MPEG-2 / MPEG-4 / H.264)
- Conditional Access Interface (smartcard reader)
- DiSEqC supported
- USB WIFI and LAN support YOUTUBE, Weather Forecast, Internet Radio, Google Map, RSS reader etc..
- Full HD output in 576i, 576p, 720p, 1080i, 1080p
- UniCable supported
- Multi satellite search, network search, Multi TP search, Blind search supported
- 32 bits True Color On Screen Display (OSD)
- 8 Favorite group and parental lock supported
- 7 days EPG supported
- Multi language MENU/OSD support (English, German, Turkish, Polish, Italian, Dutch etc....)
- Multi Language audio
- Multi Language DVB Subtitle output
- Timer function supported
- Low Power Consumption design

Specifications



Processor & Memory

- Flash: 8MB
- SDRAM: 128MB

Tuner & Channel

- Tuner: Input frequency range: 950-2150MHz
- Input impedance: 75 Ohm
- Demodulation: QPSK
- Tuner: GST GS4L-01
- Symbol rate: 2.0 ~45 MS/s

Audio

- Standard: ISO/IEC 13818-3
- Sampling Frequency: 32, 41.1, 48KHz
- Audio Output Impedance: Low
- Output Mode: Mono, Dual Channel, Stereo, Left and Right

Video

- Standard: ISO/IEC 13818-2
- MPEG-1, MPEG-2 MP@ML
- Video Full resolution: 720 x 480i, 720 x 576i, for SD video, dual
- MPEG-1, MPEG-2 decode for SD resolution

A/V Output

- Video De-emphasis: CCIR TEC: 405-1, 625 lines
- Video Bandwidth: 5,5 MHz
- Video Output impedance: 75 Ohm'
- Video Output level: 1.0Vpp
- Audio Output frequency: 20Hz ~ 20KHz

Data In/Out

- Video connectors: AV Out, RF
- Other connectors: 1 * USB, Tuner In/Out, RS232, HDMI

Power Supply

- Input Voltage: 12VDC / Adapter AC 100 ~ 240V, 50/60Hz
- Power Consumption: Max. 20W